

2009 No. 3224 (W.278)

CLEAN AIR, WALES

**The Smoke Control Areas
(Exempted Fireplaces) (Wales)
Order 2009**

EXPLANATORY NOTE

(This note is not part of the Order)

Section 20 of the Clean Air Act 1993 (“the 1993 Act”) places a general prohibition on the emission of smoke in smoke control areas.

The Welsh Ministers may, by order made under section 21 of the 1993 Act, exempt specified classes of fireplace from the provisions of section 20, if they are satisfied that such fireplaces can be used for burning fuel other than authorised fuels without producing any smoke or a substantial quantity of smoke.

This Order applies in relation to Wales.

This Order revokes and replaces with amendments the Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2008 (S.I. 2008/3101 (W.275)).

Article 2 of the Order exempts the classes of fireplaces listed in the first column of the Schedule to the Order from the provisions of section 20 of 1993 Act, subject to the conditions in the second column of that Schedule.

A regulatory impact assessment has been prepared in connection with this Order. A copy can be obtained from the Welsh Assembly Government, Cathays Park, Cardiff, CF10 3NQ.

2009 No. 3224 (W.278)

CLEAN AIR, WALES

**The Smoke Control Areas
(Exempted Fireplaces) (Wales)
Order 2009**

Made 4 December 2009

Laid before the National Assembly for Wales

8 December 2009

Coming into force 31 December 2009

The Welsh Ministers in exercise of the powers conferred upon the Secretary of State by section 21 of the Clean Air Act 1993⁽¹⁾ and now vested in the Welsh Ministers⁽²⁾, and being satisfied that the classes of fireplace exempted by this Order can be used for burning fuel other than authorised fuels without producing any smoke or a substantial quantity of smoke, hereby make the following Order:

Title, commencement and application

1.—(1) The title of this Order is the Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2009 and it comes into force on 31 December 2009.

(2) This Order applies in relation to Wales.

Classes of Fireplaces exempted from Section 20 of the Clean Air Act 1993

2. The classes of fireplaces described in the Schedule are, subject to the conditions listed, exempted from the provisions of Section 20 of the

(1) 1993 c.11.

(2) The relevant powers of the Secretary of State were transferred to the National Assembly for Wales by Article 2 of, and Schedule 1 to, the National Assembly for Wales (Transfer of Functions) (Order) 1999 (S.I. 1999/672) and thereafter transferred to the Welsh Ministers by Section 162 of, and paragraph 30 of Schedule 11 to, the Government of Wales Act 2006 (c.32)

Clean Air Act 1993 (which prohibits smoke emissions in smoke control areas).

Revocation

3. The Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2008 (S.I. 2008/3101 (W.275)) is revoked.

Jane Davidson

Minister for Environment, Sustainability and Housing,
one of the Welsh Ministers

4 December 2009

SCHEDULE
CLASSES OF FIREPLACE WHICH
ARE EXEMPT

Article 2

<i>Classes of Fireplace</i>	<i>Conditions</i>
<p>The Binder Wood Fired Boiler models RRK 22-49 (49 kW output) manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's and Wood Energy Limited's instructions entitled Binder Equipment Installation, Commissioning and Maintenance dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0.</p> <p>2. No fuel is to be used other than wood pellets or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>The Binder Wood Fired Boiler models RRK 80-175 (75-149 kW output) with cyclone models ZA 80-175 manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's and Wood Energy Limited's instructions entitled Binder Equipment Installation, Commissioning and Maintenance dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0.</p> <p>2. No fuel is to be used other than wood pellets or</p>

wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Binder Wood Fired Boiler model RRK 130-250 (185-230 kW output) 200-350 (250-300 kW output) 400-600 (350-500 kW output) 640-850 (650-840 kW output) with cyclone (model type ZA) manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's and Wood Energy Limited's instructions entitled Binder Equipment Installation, Commissioning and Maintenance dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0.

2. No fuel is to be used other than wood pellets or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Binder Wood Fired Boiler model RRK 1000 (1200 kW output) with multi-cyclone (model MZA) manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's and Wood Energy Limited's instructions entitled Binder Equipment Installation, Commissioning and Maintenance dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0.

2. No fuel is to be used other than wood pellets or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-

preservatives or coatings.

The Binder Wood Fired Boiler model RRK 1200-1650 (1650 kW output) with Binder model MZA multi-cyclone and automatic ignition manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH), Mitterdorfer Strasse 5, A-8572 Barnbach, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's and Wood Energy Limited's Operating instructions for Binder appliances referenced; 2009 July Binder O & M revision 8.doc Operation and Maintenance Manual, revision 8, dated 15 July 2009.

2. No fuel is to be used other than wood pellets or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Binder Wood Fired Boiler model RRK 1800-2300 (2100 kW output) with Binder model MZA multi-cyclone and automatic ignition manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH), Mitterdorfer Strasse 5, A-8572 Barnbach, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's and Wood Energy Limited's Operating Instructions for Binder appliances referenced; 2009 July Binder O & M revision 8.doc Operation and Maintenance Manual, revision 8, dated 15 July 2009.

2. No fuel is to be used other than wood pellets or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Binder Wood Fired Boiler model RRK 2500-3000 (3000 kW output) with Binder model MZA multi-cyclone and automatic ignition

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's

manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH), Mitterdorfer Strasse 5, A-8572 Barnbach, Austria

and Wood Energy Limited's Operating Instructions for Binder appliances referenced; 2009 July Binder O & M revision 8.doc Operation and Maintenance Manual, revision 8.doc, dated 15 July 2009.

2. No fuel is to be used other than wood pellets or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Biomatic 220 and 250 fitted with Zyklovent 220-250 cyclone separator manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Sebersdorf 138, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated April 2005, reference Bedienungsanleitung Englisch v2.0 doc.

2. No fuel is to be used other than wood chips, wood pellets, or planed wood shavings, but excluding any such chips or pellets or shavings which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Biomatic 300,350, 400 and 500 fitted with Zyklovent 300-500 cyclone separator manufactured by HERZ Armaturen Ges m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Seberdorf 138, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated April 2005, reference Bedienungsanleitung Englisch v2.0 doc.

2. No fuel is to be used other than wood chips, wood pellets, or wood shavings but excluding

any such pellets or chips or shavings which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Carron Stove manufactured by Jig UK Limited, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual reference '91-62351' dated July 2009.

2. No fuel is to be used other than dry and split wood logs of a maximum length of 23cm but excluding any such dry and split wood logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Clearview Pioneer 400, Solution 400 and Pioneer Oven wood burning stoves fitted with a tamperproof mechanical stop on the air slide/damper manufactured by Clearview Stoves of More Works, Bishops Castle, Shropshire, SY9 5HH

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions entitled 'Operating Instructions Clearview Vision/Vision Inset/Pioneer & Solution' dated 1 July 2006, reference V1/42, stamped and signed "Smoke Control".

2. No fuel is to be used other than air-dried wood logs, but excluding any such logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Contura 510, 520T, 550, 550A, 550W, 560T, 560K, 570, 580, 585, 590, Contura T, all manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's installation instructions

IAV SE/EX 0726-6
611821; Lighting
instruction BAV SA/EX
0717-2 611820

A permanent stop must be in place on the air inlet to prevent closure beyond a minimum air open position.

2. No fuel is to be used other than untreated dry wood with less than 20% moisture, but excluding any such dry wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preserved or coatings.

Contura 580W manufactured by
NIBE AB Box 134, 285 23
Markaryd, Sweden

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's installation instructions IAV SE/EX 0740-1 511911

A permanent stop must be in place on the air inlet to prevent closure beyond a minimum air open position.

2. No fuel is to be used other than untreated dry wood with less than 20% moisture, but excluding any such dry wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preserved or coatings.

Cove 2 SR manufactured by A J
Wells and Sons Ltd, Bishops Way,
Newport, Isle of Wight, PO30 5WS

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual reference 'Cove2SR 07.09 IssB' dated July 2009

A permanent stop must be in place on air control to prevent closure beyond 14mm from the fully closed position.

2. No fuel is to be used other than dry and split wood logs of a maximum length of 23cm, but excluding any such dry and split wood logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The CTC Ecoflex 15 and 20 manufactured by Enertech AB, Box 313, S-341 26 Ljungby, Sweden

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 20 February 2007, reference 161 505 27 06/1.

2. No fuel is to be used other than wood pellets but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Dovre 250 (model DV-250) manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions, reference PM250 Issue 1.

A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 75% open position.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of

The Dunsley Yorkshire Stove,
manufactured by Dunsley Heat
Limited, Bridge Mills, Huddersfield
Road, Holmfirth, Yorkshire, HD9
3TW

treatment with wood-
preservatives or coatings.

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 5 August 1998, reference A/22160 as amended by those dated 4 December 2004, reference D13.

2. No fuel is to be used other than:

- Untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings
- Peat or peat briquettes with, in either case, less than 25% moisture
- Union Coal Briquettes, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight
- CPL wildfire, manufactured by Coal Products Ltd, Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by

a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight.

The Dunsley Yorkshire Multifuel Stove manufactured by Dunsley Heat Limited, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 5 August 1998, reference A/22160 as amended by those dated 4 December 2004, reference D13.

2. No fuel is to be used other than:

- Untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings
- Peat or peat briquettes with, in either case, less than 25% moisture
- Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight
- CPL wildfire, manufactured by Coal Products Ltd, Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approximately 96%

of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from these constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight

The Dunsley Yorkshire Multifuel Stove and Boiler manufactured by Dunsley heat Limited, Bridge Mills, Huddersfield Road, Homfirth, Yorkshire HD9 3TW

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 5 August 1998, reference A/22160 as amended by those dated 4 October 2004, reference GHD/DUN4B/1

2. No fuel is to be used other than:

- Untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings
- Peat or peat briquettes with, in either case, less than 25% moisture
- Union Coal Briquettes, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight
- CPL wildfire, manufactured by Coal

Products Ltd, Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight.

The Dunsley Yorkshire Woodburning Stove manufactured by Dunsley Heat Limited, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 4 December 2004, reference D13W.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservedatives or coatings.

The Dunsley Yorkshire Woodburning Stove and Boiler manufactured by Dunsley Heat Limited, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 4 December 2004, reference D13W together with manufacturer's instructions dated 4 October 2004, reference GHD/DUN4B/1.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains

halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Extraflame:
Babyfiamma
Bella and Bella Lux
Clementia
Comfort Maxi
Contessa
Divina, Divina Plus and Divina Steel
Duchessa and Duchessa Steel
Ecologica
Esmeralda and Esmeralda Crystal
Falò 1CP, Falò 2CP and Falò 1XP
Isabella
Karolina
Preziosa
All of which are manufactured by
Extraflame S.p.a in Montecchio
Precalcino (Vicenza), Italy

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 5 March 2007, reference 004275101 011.

2. No fuel is to be used other than wood pellets, but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Extraflame Comfort Mini
manufactured by Extraflame S.p.a in
Montecchio Precalcino (Vicenza),
Italy

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 2 October 2006, reference 004275 115 REV 005.

2. No fuel is to be used other than wood pellets, but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Extraflame Idro manufactured
by Extraflame S.p.a in Montecchio
Precalcino (Vicenza), Italy

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 28 August 2006, reference 004275128 REV 002.

2. No fuel is to be used other than wood pellets, but excluding any such pellets which contain halogenated organic

The Extraflame Lucrezia Idro and Lucrezia Steel manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy

compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 12 July 2006, reference 004275110 REV 011.

2. No fuel is to be used other than wood pellets, but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Firematic 25, 50, 90 and 150 manufactured by HERZ Aramtüren Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Sebersdorf 138, Austria

1. The fireplaces must be installed, maintained and operated in accordance with the manufacturer's instructions dated June 2005, reference Bedienungsanleitung Firematic V 1.1 ENG doc.

2. No fuel is to be used other than chipped wood, wood pellets, or planed wood shavings, but excluding any such wood, pellets or shavings which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Franco Belge Model 134 08 11 Savoy EA (8 kW output) wood burning stove manufactured by Franco Belge, Staub Fonderie SARL, Rue Orphée Variscotte, 59660, Merville, France

1. The fireplace must be installed, maintained and operated in accordance with the Savoy EA Technical Manual, document reference 1290-1, reviewed 9 July 2009.

2. No fuel is to be used other than wood logs, but excluding any such wood logs which contain

halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Fröling Turbomat 28, 35, 48 and 55 manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H, Industriestrasse 12, A-4710 Grieskirchen, Austria

1. The fireplace must be installed in accordance with the manufacturer's installation instructions dated November 2003, reference M 060 01 03.

The fireplace must be maintained and operated in accordance with the manufacturer's operating manual dated August 2002, reference 99229a.

2. No fuel is to be used other than wood chips with less than 35% moisture content that meet ONORM (a) M 7133; 1998 size class G30 or wood pellets of 6mm diameter and a moisture content below 10% but excluding any such chips or pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Fröling Turbomat 85, 100 and 110 manufactured by Fröling Heizkessel-und Behälterbau Ges.m.b.H, Industriestrasse 12, A-4710 Grieskirchen, Austria

1. The fireplace must be installed in accordance with the manufacturer's installation instructions dated November 2003, reference M 060 01 03.

The fireplace must be maintained and operated in accordance with the manufacturer's operating manual dated August 2002, reference 99229a.

2. No fuel is to be used other than wood chips with less than 35% moisture content that meet ONORM (a) M

7133; 1998 size class G30 or G50, wood pellets of 6mm diameter and a moisture content below 10%, but excluding any such chips and pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preserved or coatings.

The Fröling Turbomat 150 and 220 manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H, Industriestrasse 12, A-4710 Grieskirchen, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated August 2003, reference B0310003.

2. No fuel is to be used other than wood pellets, or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preserved or coatings.

The Fröling Turbomat 320 and 500 manufactured by Fröling Heizkessel und Behälterbau Ges.m.b.H, Industriestrasse 12, A-4710 Grieskirchen, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated November 2004, reference B0340004.

2. No fuel is to be used other than wood pellets, or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preserved or coatings.

Fröling P4 8, 15, 20, 25, 32, 38, 48 and 60 Pellet Boilers manufactured by Fröling Heizkessel und Behälterbau Ges.m.b.H, Industriestrasse 12, A-4710

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual

Grieskirchen, Austria

reference "B0430408_en"
dated July 2009.

2. No fuel is to be used other than wood pellets with a diameter of 6mm, but excluding any such wood pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Gilles HPK-RA 13kW, 15kW, 20kW, 25kW, 30kW, 35kW, 40kW, 45kW, 49kW, 60kW, 70kW, 75kW, 85kW, 95kW, 100kW, 120kW, and 145kW, all manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated January 2007, reference Gilles/0-145/1.

2. No fuel is to be used other than wood pellets, or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Gilles HPK USK 150kW, 180kW, 240kW and 300kW, manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated January 2007, reference Gilles/150-300/1.

2. No fuel is to be used other than wood pellets, or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Gilles HPK USK 360kW manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's

Gmunden, Austria

operating instructions dated January 2008, reference Gilles 360/1.

2. No fuel is to be used other than wood pellets or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Gilles UTSK 450kW, 550kW, 700kW, 900kW, 1200kW and 1600kW Boilers manufactured by GILLES Energie-und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's operating instructions dated January 2008, reference 360/1.

2. No fuel is to be used other than wood pellets or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Guntamatic Biocom and Powercorn 50 and 75 manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual reference "GUN/BIO/OP/VI/0709" dated 29 July 2009.

2. No fuel is to be used other than wood pellets with a diameter of 6mm and a length of between 10 and 30mm but excluding any such wood pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Guntamatic Powerchip 50 and 75
manufactured by GUNTAMATIC
Heiztechnik GmbH A-4722
PEUERBACH Bruck 7

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions manual reference "GUN/POW/OP/VI/0709" dated 29 July 2009.

2. No fuel is to be used other than wood pellets with a diameter of 6mm and a length of between 10 and 30mm but excluding any such wood pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Guntamatic Biocom and Powercorn
100 manufactured by
GUNTAMATIC Heiztechnik GmbH
A-4722 PEUERBACH Bruck 7

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual reference "GUN/BIO/OP/VI/0709" dated 29 July 2009.

2. No fuel is to be used other than wood pellets with a diameter of 6mm and a length of between 10 and 30 mm, or wood chip with less than 35% moisture content and meeting ONORM M 7133:1998 size class G30, but excluding any such wood pellets or wood chip which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Guntamatic Powerchip 100
manufactured by GUNTAMATIC
Heiztechnik GmbH A-4722
PEUERBACH Bruck 7

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual reference "GUN/POW/OP/VI/0709" dated 29 July 2009.

2. No fuel is to be used other than wood pellets with a diameter of 6mm and a length of between 10 and 30 mm, or wood chip with less than 35% moisture content and meeting ONORM M 7133: 1998 size class G30, but excluding any such wood pellets or wood chip which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Hamont CATfire 350 USZI pellet boiler fitted with CATfirte 300 cyclone, manufactured by Hamont Contracting and Trading, spol. s.r.o., Sedlište 227, postal code 739 36, district Frýdek-Místek Czech Republic

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's operating instruction reference "Operating Manual for Boilers CATfire 150-500kW" effective from 1 January 2008.

2. No fuel is to be used other than wood pellets with a diameter of 6mm and a maximum length of 30mm but excluding any such wood pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Handöl 31, Handöl 31A, Handöl 32, Handöl 32A, Handöl 33T, Handöl 34T, Handöl 35T, Varde Ovne Look 1, Varde Ovne Look 2, Varde Ovne Look 2, all manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's installation instructions IAV SE/EX 0811-4 511941 and Lighting instructions BAV SE/EX H30 511942

A permanent stop must be in place on the air inlet to prevent closure beyond a minimum air open

position.

2. No fuel is to be used other than untreated dry wood with less than 20% moisture, but excluding any such dry wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Handöl 50, Handöl 51, Handöl 52, Handöl 52T, Handöl 53, Handöl 54, Handöl 54T, Handöl 51L, Varde Ovne S1, Varde Ovne S2, Varde Ovne S3, all manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's installation instructions IAV SE/EX 0737-4 511866 and Lighting instructions BAV SE/EX 0717-1 511865

A permanent stop must be in place on the air inlet to prevent closure beyond a minimum air open position.

2. No fuel is to be used other than untreated dry wood with less than 20% moisture, but excluding any such dry wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Highlander 5 Clean Burn manufactured by Dunsley Heat Limited, Brdige Mills, Huddersfield, Holmfirth, West Yorkshire, HD9 3TW

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual reference "Highlander: The Dunsley-Enviroburn-5. Clean Burn Stove Installation and operating instructions D12-01-09, D060-01-09, D13-01-09, D12-12-08"

2. No fuel is to be used other than wood logs

conforming to BS EN 13240:2001, but excluding any such wood logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preserved or coatings.

The Hoval BioLyt 50 Wood Pellet Boiler (49kW thermal output) manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's technical information and installation instructions dated October 2005, reference 4 204794/00 and operating instructions dated January 2006, reference 4 204 793/01.

2. No fuel is to be used other than wood pellets, but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preserved or coatings.

The Hoval BioLyt 50 and 70 models manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's technical information and installation instructions dated June 2007, reference 4 204 794/01 and 4 204 793/02.

2. No fuel is to be used other than 6mm diameter wood pellets but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preserved or coatings.

The Hoval ArgoLyt 20, 25, 35, 45 and 50 manufactured by Hoval AG, Austrasse 70, 9490 Vaduz,

1. The fireplace must be installed, maintained and operated in accordance

Liechtenstein

with the manufacturer's technical information and installation instructions dated January 2006, reference 4 205 194/00 and 4 205 193/00 dated June 2006.

2. No fuel is to be used other than Wood logs with less than 20% moisture but excluding any such logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Hoval STU 150, 200, 250, 300, 350, 425 and 500 manufactured by Hoval UK Ltd, Northgate, Newark-on-Trent, Nottinghamshire, NG24 1JN

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's technical information and installation instructions dated November 2007, reference STUman/01 or dated June 2008, reference STU/man/01/1.

2. No fuel is to be used other than 6mm diameter wood pellets but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Hoval STU 600, 800 and 1000 manufactured by Hoval UK Ltd, Northgate, Newark-on-Trent, Nottinghamshire, NG24 1JN

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's technical information and installation instructions dated June 2008, reference STU/man/01/1.

2. No fuel is to be used other than 6mm diameter wood pellets, but excluding any such pellets which contain halogenated organic

<p>The Huntingdon 25 clear door (model number 7057) and Huntingdon 25 tracery door (model number 7058) manufactured by Stovax Limited, Falcon Road, Sowerton Industrial Estate, Exeter, Devon EX2 7LF</p>	<p>compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual, reference PM 249 Issue 1.</p>
	<p>A permanent stop must be in place on the secondary inlet to prevent closure beyond the 75% open position.</p>
	<p>2. No fuel is to be used other than untreated dry wood but excluding any such wood which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>The Hwam Beethoven, The Hwam Beethoven H, Hwam Mozart, Hwam Ravel, Hwam Vivaldi, Hwam 30 (4.5kW nominal thermal output) fitted with mechanism to prevent closure of the air wash-secondary air control manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Horning, Denmark</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference IN1 141 Ed B.</p>
	<p>2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>The KWB TDS Powerfire 130, 240 and 300 manufactured by KWB-Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH) of Industriestrasse 235, A/8321 St. Margarethen an der Raab</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 14 May 2008, reference BA TDS-05.2008 including specification of</p>

recommended fuels.

2. No fuel is to be used other than wood pellets or wood chips but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The KWB TDS Powerfire 150 manufactured by KWB-Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarthen an der Raab

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated August 2005, reference BA TDS-0805.

2. No fuel is to be used other than wood pellets or wood chips, but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Little Wenlock Classic Wood Fuel Stove, manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's operating instructions dated 19 December 2008, reference N00471AXX Rev 001 DP 081219

2. No fuel is to be used other than dry and split wood logs of a maximum length of 25cm and a maximum diameter of 10cm, but excluding any such dry and split wood logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Little Thurlow wood burning

1. The fireplace must be

stove manufactured by Town and Country Fires Pickering, North Yorkshire

installed, maintained and operated in accordance with the manufacturer's instructions dated 30 June 2007, issue No.3.

2. No fuel is to be used other than seasoned logs of less than 20% moisture and of a maximum length of 350mm, but excluding any such logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Løvenholm manufactured by Hunter Stoves Ltd, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ

1. The fireplace must be installed, maintained and operated in accordance with Løvenholm Multifuel stove installation and operation manual version 07/08.

2. No fuel is to be used other than untreated wood with less than 20% moisture content but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Løvenholm, Løvenholm Traditional, Løvenholm European, and Løvenholm Pedestal Stoves manufactured by Hunter Stoves Ltd, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon, EX5 4RJ

1. The fireplace must be installed, maintained and operated in accordance with Løvenholm Multifuel stove installation and operating manual version 06/09.

2. No fuel is to be used other than untreated wood with less than 20% moisture content but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-

preservatives or coatings.

The Mescoli PB50, PB35, PB28, manufactured by MESCOLI CALDAIE S.r.l. Caldaie-Termocucine, Via del Commercio, 285 4 1058 Vignola, (MO) Italy

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction and installation manual reference "SY315EVO P,C,B-COMBIFIRE 2 PB28/35/50 BOILERS" Edition 1.7 Dated 1/2006.

2. No fuel is to be used other than wood pellets following ONORM M7 135 or DIN plus (DFIN 51731) but excluding any such wood pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Morsø 1400 series consisting of the 1412 and 1442 models manufactured by Morsø Jernestoberi A/S DK-7900 Nykobing, Mors, Denmark

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's installation and operating manual dated 10 January 2008, reference 72146800.

2. No fuel is to be used other than wood logs with less than 20% moisture, but excluding any such logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Morsø 3100 series consisting of the 3112 and 3142 models manufactured by Morsø Jernestoberi A/S DK-7900 Nykobing, Mors, Denmark

1. The fireplace must be installed, maintained and operated in accordance with the installation and operating manual dated 4 February 2008, reference 723 11200.

2. No fuel shall is to be used other than wood logs with less then 20%

moisture, but excluding any such logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Morsø 6140 and 6148 manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 4 September 2007, reference 72610400.

2. No fuel is to be used other than wood logs with less than 20% moisture, but excluding any such logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Morsø Owl 3410, 3420 and 3440 for wood burning manufactured by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 1 January 2000, reference 72345600.

2. No fuel is to be used other than untreated dry wood which has been split, stacked and air dried; or air dried wood briquettes but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Nestor Martin Harmony Multi-Fuel Stove H13 (3.5 kW nominal thermal output) and H33 (8kW nominal thermal output) manufactured by Nestor Martin, S A Finuick Ny, Voie Axiale 5, B-5660 Couvin, Belgium

1. The fireplace must be installed, maintained and operated in accordance with Euroheat Distributors (HBS) Limited's operational instructions dated January 2007, reference IN1 116

Edition D.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Nestor Martin Harmony Multi-Fuel Stove H23 (6kW nominal thermal output) manufactured by Nestor Martin, S A Finuick Nv, Voie Axiale 5, B-5660 Couvin, Belgium

1. The fireplace must be installed, maintained and operated in accordance with Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference IN1 141 Edition B.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Nestor Martin Stanford Multi-Fuel Stove S13, S23 and SP23 (6kW nominal thermal output) manufactured by Nestor Martin, S A Finuick NV, Voie Axiale 5, B/5660 Couvin, Belgium

1. The fireplace must be installed, maintained and operated in accordance with Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference IN1 141 Edition B.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Nestor Martin Stanford Multi-Fuel Stove S13 (3.5 kW nominal

1. The fireplace must be installed, maintained and

thermal output), S33 and SP33 (8kW nominal output) manufactured by Nestor Martin, S A Finuick Nv, Voie Axiale 5, B-5660 Couvin, Belgium

operated in accordance with Euroheat Distributors (HBS) Limited's operational instructions dated January 2007, reference IN1 116 Edition D.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Nestor Martin R23 Stove (6kW nominal thermal output) manufactured by Nestor Martin, S A Finuick Nv, Voie Axiale 5, B-5660 Couvin, Belgium

1. The fireplace must be installed, maintained and operated in accordance with Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference IN1 141 Edition B.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Nestor Martin Multi-fuel Stove IT 13 (3.5 kW nominal thermal output) manufactured by Nestor Martin, S A Finuick Nv, Voie Axiale 5, B-5660 Couvin, Belgium

1. The fireplace must be installed, maintained and operated in accordance with Euroheat Distributors (HBS) Limited's operational instructions dated April 2007, reference IN1 180 Edition C.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of

	treatment with wood-preservatives or coatings.
The Nestor Martin Multi-fuel Stove R33 and D33 (8kW nominal thermal output) manufactured by Nestor Martin, S A Finuick Nv, Voie Axiale 5, B/5660 Couvin, Belgium	<p>1. The fireplace must be installed, maintained and operated in accordance with Euroheat Distributors (HBS) Limited's operational instructions dated January 2007, reference In1 116 Edition D.</p> <p>2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
The Ökofen Pellematic PE08, PE12, PE16, PE20, PE25, PE32, PEK12, PEK16, PEK20, PEK25, PEK32, PES12, PES16, PES20, PES25, PES32, PESK12, PESK16, PESK25 and PESK32 manufactured by Ökofen Forschungs-und Entwicklungs Ges.m.b.H of Gewerberpark 1, 4133 Niederkappel, Austria	<p>1. The fireplace must be installed, maintained and operated in accordance with Ökofen operating instructions dated February 2007 reference PE/HB/001.E</p> <p>2. No fuel is to be used other than wood pellets with a maximum diameter of 6mm and a maximum length of 4cm but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
The Ökofen Pellematic PE36, PE48, PE56, PESK36, PESK48, PESK56, PEK36, PEK48, PEK56, PES36, PES48 and PES56 manufactured by Ökofen Forschungs-und Entwicklungs Ges.m.b.H of Gewerbepark 1, 4133 Niederkappel, Austria	<p>1. The fireplace must be installed, maintained and operated in accordance with Ökofen operating instructions dated March 2008, reference PBV 2000 CMP 1.4 (V2.31)</p> <p>2. No fuel is to be used other than wood pellets with a maximum diameter of 6mm and a maximum</p>

length of 4cm but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Orchard Ovens models: FVR Speciale 80, 100, 110, 110 x 160 and 120; TOP Superiore 100 and 120; GR 100, 120, 140, 120 x 160, 140 x 160, 140 x 180 and 180; OT 100, 120, 140, 120 x 160, 140 x 160, 140 x 180 and 180; the Valoriani Piccolo, all of which are manufactured by Valoriani of Via Caselli alla Fornace, 213 50066 Reggello, Firenze, Italy

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 25 October 2004, references:

Instruction	Model
OOLinst.1	FVR 80
OOLinst.2	FVR 100
OOLinst.3	FVR 110
OOLinst.4	FVR 120
OOLinst.5	FVR 110 x 160
OOLinst.6	TOP 100
OOLinst.7	TOP 120
OOLinst.8	GR 100 and OT 100
OOLinst.9	GR 120 and OT 120
OOLinst.10	GR 140 and OT 140
OOLinst.11	GR 120 x 160 and OT 120 x 160
OOLinst.12	GR 140 x 160 and OT 140 x 160
OOLinst.13	GR 140 x 180 and OT 140 x 180
OOLinst.14	GR 180 and OT 180
OOLinst.15	Valoriani Piccolo

2. No fuel is to be used other than untreated dry wood but excluding any

<p>Pellestar 10, 20, 30, 45 and 60 manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ Feuerungstechnik, A-8272 Sebersdorf 138, Austria</p>	<p>such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>The Quadra-Fire 2100 Millennium Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's operating instructions dated November 2007, reference V2.2</p> <p>2. No fuel is to be used other than wood pellets corresponding to ONORM M7135 of 6mm diameter, but excluding any such wood pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>The Quadra-Fire Yosemite Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 9 October 2003, reference 250-6931B.</p> <p>2. No fuel is to be used other than dry cured untreated wood of maximum size 38.1cm x 10.16 cm x 5.08 cm, but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>The Quadra-Fire Yosemite Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 4 June 2003, reference 7004-187</p>

2. No fuel is to be used other than dry cured untreated wood of maximum size 38.1cm x 10.16cm x 5.08cm, but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Quadra-Fire Cumberland Gap Freestanding Wood Burning Stove manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 8 July 2003, reference 7006-186.

2. No fuel is to be used other than dry cured untreated wood of maximum size 43.18cm x 10.16cm x 5.08cm but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Redfyre Kensal 20 Flat top (product code RF-EN20M), Redfyre Kensal 33 Flat top (product code RF-KEN 33M and RF-KEN 33W) manufactured by Redfyre Cookers, Osprey Road, Sowton Industrial Estate, Exeter, Devon, EX2 7JG

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual dated July 2008, reference PM247 issue 1, and instruction manual dated January 2009, reference PM280 issue 1.

A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.

2. No fuel is to be used other than untreated dry wood but excluding any such dry wood which contains halogenated organic compounds or

<p>The Scan Anderson 4-5 manufactured by Krog Iversen 7 Co., A/S DK-5492 Vissenbjerg, Denmark</p>	<p>heavy metals as a result of treatment with wood- preservatives or coatings.</p>
	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer’s instructions dated 15 November 2007, entitled “Scan Anderson 4-5” reference 09/05-GB.</p>
	<p>A permanent stop must be in place on the secondary air inlet to prevent closure beyond 20mm.</p>
	<p>2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Schmid UTSK 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600kW manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon.</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer’s “Instruction manual UTSK-ABC.22-AME-S- PPU” dated 25 September 2008 where ABC is model number i.e. 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600.</p>
	<p>2. No fuel is to be used other than wood pellets or wood chips following CEN/TS 14961 but excluding any such wood pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.</p>
<p>Schmid UTSL 30, 40, 50, 65, 80, 110, 150kW manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH/8380 Eschikon</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer’s</p>

instruction manual
reference “Operating
Manual Wooden Chips
and Pellets
Plant.Lignumat UTSL”
dated 23 December 2004.

2. No fuel is to be used
other than wood pellets or
wood chips following
CEN/TS 14961 but
excluding any such wood
pellets or chips which
contain halogenated
organic compounds or
heavy metals as a result of
treatment with wood-
preservatives or coatings.

Schmid UTSP 180, 240, 300kW
manufactured by Schmid AG
Woodfiring Systems, PO Box 42,
CH-8380 Eschikon

1. The fireplace must be
installed, maintained and
operated in accordance
with the manufacturer’s
“Instruction manual
UTSK-ABC-22-AME-S-
PPU” dated 25 September
2008 where ABC is
model number i.e. 180,
240, 300.

2. No fuel is to be used
other than wood pellets
following CEN/TS 14961
but excluding any such
wood pellets which
contain halogenated
organic compounds or
heavy metals as a result of
treatment with wood-
preservatives or coatings.

Schmid UTSR 150, 180, 240, 300,
360, 450, 550, 700, 900kW
manufactured by Schmid AG
Woodfiring Systems, PO Box 42,
CH-8380 Eschikon

1. The fireplace must be
installed, maintained and
operated in accordance
with the manufacturer’s
‘instruction manual
UTSR-ABC-22-AME-S-
PPV’ dated 25 September
2008 where ABC is
model number i.e. 150,
180, 240, 300, 360, 450,
550, 700, 900.

2. No fuel is to be used
other than wood pellets or
wood chips following

CEN/TS 14961 but excluding any such wood pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Stockton 5 flat top (model number 7119) Stockton 5 Canopy (model number 7160) and Stockton 5 Midline (model number 7133) manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon EX2 7LF

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions reference, PM176-issue 4.

A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Stockton 3 flat top (product code 7118) Stockton 4 flat top (product codes 7101 and 7102) and Stockton 5 flat top (product code 7127) Stockton 5 midline (product code 7130) Stockton 6 flat top (product codes 7100 and 7162) Stockton 6 Highline (product code 7117), Stockton 7 flat top (product codes 7120 and 7163) manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon EX2 7LF

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual dated July 2008 reference PM227 ENG Issue 2, and instruction manual dated January 2009, reference PM271 Issue 2.

A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of

treatment with wood-preservatives or coatings.

Stockton 7 Inset Convector (product codes 7125F and 7125C) manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual dated May 2008, reference PM230 Issue 1, and instruction manual dated January 2009, reference PM281 Issue 1.

A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.

2. No fuel is to be used other than untreated dry wood but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Twin Heat CS 150i manufactured by TWIN HEAT A/S, Norrevangen 7, DK-9631 Gedsted, Denmark

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's operating instructions dated 17 December 2008, reference version 6.0.03.

2. No fuel is to be used other than wood pellets of a maximum length of 30mm and diameter of 6mm and conforming to CEN/TS 14961:2005, but excluding any such wood pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Type USV wood pellet and wood chip fired boilers, model numbers USV-15, 25, 30, 40, 50, 60, 80 and 100, manufactured by KWB-

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's

Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria

instructions dated August 2003, reference BA-USV 0803.

2. No fuel is to be used other than wood pellets or wood chips but excluding any such pellets or chips which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Type USP wood pellet fired boilers model numbers USP-10, 15, 20, 25 and 30, manufactured by KWB-Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 28 July 2003 reference BA-USP 0703.

2. No fuel is to be used other than wood pellets but excluding any such pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Westfire Uniq 15, 16 and 20 (also known as WF UNIQ 15, 16 and 20) manufactured by Westfire Tømmervej 3 DK-6800 Varde, Denmark

1. The fireplace must be installed, maintained and operated in accordance with the installation and operating instructions dated 2007, reference WF15-WF16-WF20 along with supplementary instructions reference 01 wfuk.2207.

A permanent stop must be in place on the secondary air inlet to prevent closure beyond 50mm.

2. No fuel is to be used other than untreated dry wood, but excluding any such wood which contains halogenated organic compounds or heavy metals as a result of

<p>The Windhager Bio Win 90 and 120 manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str.20, A-5201 Seekirchen bei Salzburg, Austria</p>	<p>treatment with wood-preservatives or coatings.</p>
<p>The Windhager Bio Win100, 150, 210 and 260, manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str.20, A-5201 Seerkirchen bei Salzburg, Austria</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated August 2008, reference 092125/00.</p> <p>2. No fuel is to be used other than wood pellets but excluding any such wood pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p>
<p>The Wood Waste Technology Heater, models WT10 and WT15, manufactured by Wood Waste Technology Units, Units 1 & 2 Drummond Road, Astonfields Industrial Estate, Stafford, Saffordshire, ST16 3HJ</p>	<p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instruction manual dated May 2008, reference 0916197/00.</p> <p>2. No fuel is to be used other than wood pellets but excluding any such wood pellets which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.</p> <p>1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 19 January 2005, reference WT10 and WT15.</p> <p>2. No fuel is to be used other than hardwood and softwood offcuts, air dried medium density fibreboards, untreated and air dried wood offcuts, but excluding any such offcuts and fibreboards which contain</p>

halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

The Wood Waste Technology Heater Ltd. WT5, manufactured by Wood Waste Technology Units 1 & 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's instructions dated 16 February 2009, reference WT5_v2.

2. No fuel is to be used other than medium density fibreboard and untreated wood offcuts, but excluding any such fibreboard and offcuts which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Xeos 5kW stove
Versions – Natur, Style, Harmony, Pur, Classic, Elegance and Stone
Xeos 8kW stove
Versions – Basic, Pur, Classic, Elegance Stone and Air Instruction Manual references
Manufactured by Specht Modulare Ofensysteme GmbH & Co, KG i.V.
Dipl – Ing.Frank Werner
Projektmanagement Bahnhofste.2 D
35116 Hatzfeld

1. The fireplace must be installed, maintained and operated in accordance with the manufacturer's "Operating and Installation Instructions Xeos 5kW/8kW Model 2008" reference; Revisions – Index 01/08 Fassung Januar 2008.

2. No fuel is to be used other than wood logs conforming to DIN 51731, but excluding any such wood logs which contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
